

Caught In Object



WCF Insurance
1.800.446.COMP
wcf.com

The following are common types of guarding available to protect employees from harm while operating equipment.

- **Safeguarding** – When deciding a guard on a device, do a risk assessment on the machine and implement engineering controls to reduce employee exposure to the hazard.
- **Guards** – Guards prevent access to the point of operation and include die enclosures and fixed, interlocked and adjustable guards.
- **Devices** – Devices control access to the point of operation hazards.
- **Control Reliability** – Control reliability is a way to ensure the integrity of the performance of guards, devices or control systems.
- **Disconnect** –All new equipment is required to have lockable disconnects
- **Starters** –All start buttons should have a ring guard around them to protect from accidental startup.
- **Covers** – All moving belts, gears, fans, chains and pulleys should be guarded up to 7 feet from the working platform level.

Insurance coverage in all states other than Utah is provided by Advantage Workers Compensation Insurance Company, a wholly owned subsidiary of Workers Compensation Fund, doing business as WCF Insurance

Caught In Object



WCF Insurance
1.800.446.COMP
wcf.com

The following are common types of guarding available to protect employees from harm while operating equipment.

- **Safeguarding** – When deciding a guard on a device, do a risk assessment on the machine and implement engineering controls to reduce employee exposure to the hazard.
- **Guards** – Guards prevent access to the point of operation and include die enclosures and fixed, interlocked and adjustable guards.
- **Devices** – Devices control access to the point of operation hazards.
- **Control Reliability** – Control reliability is a way to ensure the integrity of the performance of guards, devices or control systems.
- **Disconnect** –All new equipment is required to have lockable disconnects
- **Starters** –All start buttons should have a ring guard around them to protect from accidental startup.
- **Covers** – All moving belts, gears, fans, chains and pulleys should be guarded up to 7 feet from the working platform level.

Insurance coverage in all states other than Utah is provided by Advantage Workers Compensation Insurance Company, a wholly owned subsidiary of Workers Compensation Fund, doing business as WCF Insurance

Caught In Object



WCF Insurance
1.800.446.COMP
wcf.com

The following are common types of guarding available to protect employees from harm while operating equipment.

- **Safeguarding** – When deciding a guard on a device, do a risk assessment on the machine and implement engineering controls to reduce employee exposure to the hazard.
- **Guards** – Guards prevent access to the point of operation and include die enclosures and fixed, interlocked and adjustable guards.
- **Devices** – Devices control access to the point of operation hazards.
- **Control Reliability** – Control reliability is a way to ensure the integrity of the performance of guards, devices or control systems.
- **Disconnect** –All new equipment is required to have lockable disconnects
- **Starters** –All start buttons should have a ring guard around them to protect from accidental startup.
- **Covers** – All moving belts, gears, fans, chains and pulleys should be guarded up to 7 feet from the working platform level.

Insurance coverage in all states other than Utah is provided by Advantage Workers Compensation Insurance Company, a wholly owned subsidiary of Workers Compensation Fund, doing business as WCF Insurance